

OM 621BCD



OM 621BCD MONITOR BCD AND ACTIVE TRANSFORMER TAPPING LEADS

- 6-digit programmable projection
- Input BCD/transformer tapping lead
- Size of DIN 96 x 48 mm
- Power supply 80...250 V AC/DC

Options

- Excitation • Comparators • Data output • Analog output
- Power supply: 9...50 V AC/DC

Analog outputs will find their place in applications where further evaluating or processing of measured data is required in external devices. We offer universal analog output with the option of selection of the type of output - voltage/current. The value of analog output corresponds with the displayed data and its type and range are selectable in CM.

Standard functions

PROGRAMMABLE PROJECTION

Calibration: the type of BCD/transformer lead input may be set in „CM“

Projection: -99999...999999

OUTPUT

Relays' functions: For the tapping leads display device it is possible to set the regime of relay switching - BCD (10=10000)/BIN (10=01010)

Description

The OM 621BCD model is a 6 digit panel monitor of serial or parallel BCD/BIN signal and monitor of active transformer tapping lead, allowing for projection of transitional status and servomotor running.

The instrument is based on an 8-bit processor that secures high accuracy, stability and easy operation of the instrument.

Operation

The instrument is set and controlled by five control keys located on the front panel. All programmable settings of the instrument are realised in two adjusting modes.

Configuration menu (hereinafter referred to as CM) is protected by an optional number code and contains complete instrument setting.

User menu may contain arbitrary programming settings defined in „CM“ with another selective restriction (see, change)

All settings are stored in the EEPROM memory (they hold even after the instrument is switched off).

Options

Comparators are assigned to monitor one, two, three or four limit values with relay output. The user may select limits regime: LIMIT/DOSING/FROM-TO. The limits have adjustable hysteresis within the full range of the display as well as selectable delay of the switch-on in the range of 0...99,9 s. Reaching the preset limits is signalled by LED and simultaneously by the switch-on of the relevant relay.

Excitation is suitable for feeding of sensors and transmitters. It is isolated, with continuously adjustable value in the range of 2...24 VDC.

Data outputs are for their rate and accuracy suitable for transmission of the measured data for further projection or directly into the control systems. We offer an isolated RS232 and RS485 with the DIN MessBus/ASCII protocol.

